(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 21 July 2005 (21,07,2005)

PCT

(10) International Publication Number WO 2005/065022 A2

(51) International Patent Classification:	Not classified	(81) Designated States (unless otherwise indicated, for every
(21) International Application Number:	T/IL2004/001132	kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
(22) International Filing Date: 15 December 2	2004 (15.12.2004)	GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG

- (25) Filing Language: English
- (26) Publication Language: English (30) Priority Data:
- (71) Applicant (for all designated States except US): QUAL-ITY BY VISION LTD. (IL/IL): Kohav Yokneam, 20692 Yokneam Ilit (IL).

11 January 2004 (11.01.2004) IL

(72) Inventors; and

159801

- (75) Inventors/Applicants (for US only): LAOR, Ofer [IL/IL]; 13/7 Dafna st., 71700 Modyin (IL). MOLOCHNIKOV, Boris (IL/IL): 3/1 Hativoni st., 36831 Nesher (IL).
- (74) Agent: GOLD PATENTS & FINANCIAL SERVICES LTD.; 43, Rubinstein St., 34987 Haifa (IL).


- PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: OPTICAL APPARATUS FOR MEASURING TOOLING POSITION WITHIN A SEAMING MACHINE



so as to pass through a profile in the toolings, and a detector adapted to receive the radiation that passed through the profile. The characteristics of the toolings such as the profiles of a gap between the chuck and the roll, are processed from the detected radiation that passes through the profile.

WO 2005/065022 A2

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.